

PRIMER ACTIVE AIR

Air Entraining/Plasticizing Admixture
CYS EN 934-3:2009+A1:2012 (Table2)

Product Description

PrimerActiveAir is a type of admixture specifically designed to improve the workability of mortar by introducing microscopic air bubbles into the mixture.



Applications

PrimerActiveAir is recommended for use in all ready-mix, precast, pre-stressed and other concrete plants where deliberate air entrainment is required. For long term retarded masonry mortar it should be used in combination with **PrimerActiveRetarder**.

Applications that require high resistance to freeze/thawing cycles.

Structural Concrete works.

Promotes the distribution of microscopic air bubbles throughout the cement matrix.

Dosage:

The amount of admixture must be carefully controlled to avoid excessive air entrainment.

0.3 to 1.5kg /100 kg of cement. Before usage site trials should be carried out.

Package:

1000 lt.

Technical data:

Specific Gravity	1.01 ± 0.01
Chloride Content	Nil
Appearance	Yellow liquid
Storage condition	Store in a dry area between 5°C and 35°C. Protect from direct sunlight.
Shelf life	Original sealed container has a shelf life of 12 months if stored in the right conditions.

Product data

Safety Instructions

The product may cause skin irritation. Wear gloves and goggles and apply barrier cream to your hands. In contact with the eyes or mucous membrane, rinse immediately with plenty of warm water and seek medical attention without delay.



PRIMER

ADMIXTURE AND CONSTRUCTION MATERIAL



Admixtures

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

The user of the product must test the product's suitability for the intended application and purpose. Primer Cy LTD reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations.

For any Further Technical Information including SDS, CE LABELS and CERTIFICATES OF CONFORMITY don't hesitate to contact our QA/QC Department.
We remain at your disposal.

E-MAIL: lab@primeracm.com | Ph.+35725336671

